

	Model	9000Btu * 4
power supply	1Ph,208-230V,60Hz	
Outdoor unit	function	Cooling
		Heating
	Capacity (min-nom-max) (Btu/h)	10000/28000/34000
		9000/31000/37000
	Power input (min-nom-max) (W)	900/2600/4700
		800/2500/3000
	EER/COP (Btu/W)	10.8
		12.4
	SEER/HSPF	16
		8.2
	Body size (WXHxD) (mm)	950x840x420
	Package size (WXHxD) (mm)	1100x880x450
	N.W/G.W (kg)	75/80
	Noise(H/L) dB/A	60
	Liquid side	6(1/4")
	Gas side	9.52(3/8") 12(1/2")
	Fan Motor Speed (rpm) (H/M/L)	840/740/640
	Fan Motor RLA(A)	0.68
	Fan Motor Capacitor (uF)	3
		9+9+9+9
Model	GWHD(09)BAND3A1AI	
	GWHD(09)BAND3A1AI	
	GWHD(09)BAND3A1AI	
	GWHD(09)BAND3A1AI	
Fan Motor Speed (rpm) (H/M/L)	9K:1150/1050/900/750	
Fan Motor RLA(A)	0.17	

Indoor Unit	Fan Motor Capacitor (uF)	1
	Noise Level dB(A)	9K:38/34/31/28
	Body size (WXHxD) (mm)	770X250X190
	Package size (WXHxD) (mm)	855X330X272
	N.W/G.W (kg)	8.5/12.5
Loading Qty		83

